



Adaptador de rosca SRS



Versão A



Versão B

Rosca G	Vedação	h		Hex		Versão	Código para Pedido SRS	
		mm	pol	mm	pol			
M10x1	Junta Metálica Tipo B	15,5	0.61	17	0.67	A	SRS20-M10x1-B	
M12x1,5		15	0.59	19	0.75	A	SRS20-M12x1,5-B	
M14x1,5		15	0.59	19	0.75	A	SRS20-M14x1,5-B	
M16x1,5		8	0.31	22	0.87	A	SRS20-M16x1,5-B	
M18x1,5		15	0.59	24	0.94	A	SRS20-M18x1,5-B	
M22x1,5		10,5	0.41	27	1.06	A	SRS20-M22x1,5-B	
G <sup>1</sup> / <sub>8</sub>		15,5	0.61	17	0.86	A	SRS20-G <sup>1</sup> / <sub>8</sub> -B	
G <sup>1</sup> / <sub>4</sub>		15	0.59	19	0.75	A	SRS20-G <sup>1</sup> / <sub>4</sub> -B	
G <sup>3</sup> / <sub>8</sub>		10,5	0.41	22	0.87	A	SRS20-G <sup>3</sup> / <sub>8</sub> -B	
G <sup>1</sup> / <sub>2</sub>		10,5	0.41	27	1.06	A	SRS20-G <sup>1</sup> / <sub>2</sub> -B	
M12x1,5	Vedação de elastômero Tipo C	15	0.59	19	0.75	A	SRS20-M12x1,5-PC	
M14x1,5		15	0.59	19	0.75	A	SRS20-M14x1,5-PC	
M18x1,5		15	0.59	24	0.94	A	SRS20-M18x1,5-PC	
G <sup>1</sup> / <sub>8</sub>		16	0.63	17	0.67	A	SRS20-G <sup>1</sup> / <sub>8</sub> -PC	
G <sup>1</sup> / <sub>4</sub>		15	0.59	19	0.75	A	SRS20-G <sup>1</sup> / <sub>4</sub> -PC	
G <sup>3</sup> / <sub>8</sub>		10,5	0.41	22	0.87	A	SRS20-G <sup>3</sup> / <sub>8</sub> -PC	
G <sup>1</sup> / <sub>2</sub>		10,5	0.41	27	1.06	A	SRS20-G <sup>1</sup> / <sub>2</sub> -PC	
R <sup>1</sup> / <sub>4</sub> K	Vedante próprio para cone Tipo D necessário	13	0.51	17	0.67	A	SRS20-R <sup>1</sup> / <sub>4</sub> K-D	
R <sup>3</sup> / <sub>8</sub> K		13	0.51	19	0.75	A	SRS20-R <sup>3</sup> / <sub>8</sub> K-D	
R <sup>1</sup> / <sub>2</sub> K		8	0.31	22	0.87	A	SRS20-R <sup>1</sup> / <sub>2</sub> K-D	
1/4NPT		10	0.39	17	0.67	A	SRS20-1/4NPT-D	
1/2NPT		8	0.31	22	0.87	A	SRS20-1/2NPT-D	
7/16-20UNF	O-Ring Tipo E	9	0.35	17	0.67	A	SRS20-7/16UNF-PE	
1/2-20UNF		15	0.59	17	0.67	A	SRS20-1/2UNF-PE	
9/16-18UNF		15,5	0.61	19	0.75	A	SRS20-9/16UNF-PE	
7/8-14UNF		11	0.43	27	1.06	A	SRS20-7/8UNF-PE	
M14x1,5		14,5	0.57	19	0.75	A	SRS20-M14x1,5-PE	
M16x1,5		8,5	0.33	22	0.87	A	SRS20-M16x1,5-PE	
M22x1,5		10	0.39	27	1.06	A	SRS20-M22x1,5-PE	
M27x2		10	0.39	32	1.26	A	SRS20-M27x2-PE	
M14x1,5	Junta Metálica Tipo B	24	0.94	19	0.75	B	SRS15-M14x1,5-B	
M16x1,5		24	0.94	22	0.87	B	SRS15-M16x1,5-B	
M18x1,5		24	0.94	24	0.94	B	SRS15-M18x1,5-B	
M20x1,5		10,5	0.41	27	1.06	B	SRS15-M20x1,5-B	
G <sup>3</sup> / <sub>8</sub>		24	0.94	22	0.87	B	SRS15-G <sup>3</sup> / <sub>8</sub> -B	
G <sup>1</sup> / <sub>2</sub>		10,5	0.41	27	1.06	B	SRS15-G <sup>1</sup> / <sub>2</sub> -B	
M14x1,5		Vedação de elastômero Tipo C	24	0.94	19	0.75	B	SRS15-M14x1,5-PC
M16x1,5			24	0.94	22	0.87	B	SRS15-M16x1,5-PC
M18x1,5			24	0.94	24	0.94	B	SRS15-M18x1,5-PC
G <sup>3</sup> / <sub>8</sub>			24	0.94	22	0.87	B	SRS15-G <sup>3</sup> / <sub>8</sub> -PC